

# WIDFLO BDF-700 (Deformer for concrete admixture)

Rev0. Dec. 2022

## Description

WIDFLO BDF-700 is an effective deformer to eliminate the air in mortar or concrete. Using WIDFLOW BDF-700 is available to maintain the targeted air content in concrete or mortar. It can make less floating layer of it on the top of admixtures.

## Physical Properties

Appearance	Clear liquid
Moisture content, %	Max. 0.3
pH	5.0 ~ 7.0
Specify gravity	1.012 ± 0.040

## Dosage

It depends on the mix design and in a normal conditions, dosage : 0.1~0.4% by admixture are recommended.

## Application

WIDFLO BDF-700 is used to decrease air in concrete or mortar.

- PCE-based concrete admixtures
- All applications for air elimination

## Packaging & Storage

- 20 kg Plastic tube
- 210kg Drum
- 1MT IBC Tank



## Shelf life & Precautions

A minimum shelf life is 6 months. Depending on storage conditions, the shelf life may be longer than stated.

It is recommended to use standard handling procedures with the product. Wear gloves and eye protection and wash splashes to the skin with soap and water at the end of shifts or at breaks.

It is not hazardous, and corrosive. Comprehensive instructions are given in the Material Safety Data Sheet.

Notice. The information provided above is for general guidelines only and may change depending on the site and conditions of use. BUHUNG CONSTRUCTION CHEMICALS does not have any responsibility for injuries caused by using this material if users do not follow directions mentioned in this technical data sheet.

Tel. : +82.70 4153 6177 / Fax. : +82.504 477 9258 / E-mail: chadkwon@buhungcnc.com

